



TR001G


CORDLESS REBAR TYING TOOL



AVAILABLE AS

TR001GZ without battery and charger

PRODUCT HIGHLIGHTS



Wire pullback mechanism
The tool retracts the wire while holding its tip, ensuring tight and secure ties around the rebar. This feature improves tie quality and reduces slack, especially in demanding applications.



Rebar-compatible hook design
The hook is shaped to fit rebars up to D19 in diameter, allowing easy hanging of the tool and convenient storage of wire reels like D13, D16, and D19

x2							x3						
	D10	D13	D16	D19	D22	D25		D10 x2	D13 x2	D16 x2	D19 x2	D22 x2	D25 x2
D10	✓						D10	✓	✓	✓	✓	✓	✓
D13	✓	✓					D13	✓	✓	✓	✓	✓	
D16	✓	✓	✓				D16	✓	✓	✓	✓		
D19	✓	✓	✓	✓			D19	✓	✓	✓	✓		
D22	✓	✓	✓	✓	✓		D22	✓	✓	✓	✓		
D25	✓	✓	✓	✓	✓	✓	D25	✓	✓	✓	✓		
D29	✓	✓	✓	✓	✓	✓	D29	✓	✓	✓			
D32	✓	✓	✓	✓	✓		D32	✓	✓	✓			
D35	✓	✓	✓	✓									

x4			
	D10 x2	D13 x2	D16 x2
D10 x2	✓		
D13 x2	✓	✓	
D16 x2	✓	✓	✓

USER BENEFITS

- Suitable for: professional concrete workers, rebar installers, and construction site technicians
- Wire pullback mechanism ensures tight and secure ties by retracting the wire while holding its tip
- Dual BL motors for twisting and feeding provide stable performance with 1,6 mm annealed wire
- Clockwise wire twisting reduces the chance of loosening during manual retightening
- Easy one-step wire reel loading simplifies maintenance and speeds up workflow
- Tying strength adjustment with 6 stages allows precise control for different rebar sizes
- Fast tying speed of 0,7 s per tie increases productivity on site
- Capable of tying two, three, and four-rebar combinations
- Equipped with anti-restart function and trigger lock

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Applicable tie wire	16Ga (ø 1,6 mm)
Min./max. capacity - 2 rods	D10 x D10 / D35 x D35
Min./max. capacity - 3 rods	D10 x D10 x D10 / D32 x D32 x D32
Min./max. capacity - 4 rods	(D10 x 2) x (D10 x 2) / (D16 x 2) x (D16 x 2)
Tying speed	0,7 s
Number of ties*1	3.900
Dimensions (L×W×H)*1	375 x 113 x 331 mm
Weight*2	3,3 kg

*1 with BL4040 battery / *2 with BL4020 battery

ACCESSORIES

Tie wire (32 pcs)
1915N0-0Extension handle
1915N6-8

NOISE AND VIBRATION

Sound pressure level: **80 dB(A)**,
Sound power level: **88 dB(A)**,
Vibration level: **2,5 m/s²**

COMPATIBILITY

Recommended: **BL4020, BL4040, BL4040F and BL4050F**
Compatible: **BL4080F and BL4080H**

RELATED PRODUCTS



18 V LXT
DTR181
Cordless rebar
tying Tool



18 V LXT
DTR180
Cordless rebar
tying tool



www.makita-see.com

Makita Group reserves the right to make changes in this leaflet and the right to information in all forms and methods in connection with this leaflet. Pictures may differ from real products.